



700 Series

Pressure Control

Model WW-72S-B2H-BP

Pressure Reducing System with Hydraulic Backup Valve and Relief Device

WB2H is hydraulically operated potable water pressure reducing system that combines emergency backup valve, relief device and integral zero flow modulation. The system reduces higher upstream pressure to lower constant downstream pressure regardless of fluctuating demand or varying upstream pressure. It protects the consumers from excessive pressure and ensures continuous water supply in emergency situations. The WW-72S-WBP-B2H system consists of BERMAD 700ES valves and combines main pressure reducing valve with a "hot backup" PRV that kicks over to operation and switches an alarm signal in case of main PRV malfunction.


BERMAD water control systems for buildings combine valves and control elements into one compact, factory assembled and calibrated integral structure, designed to perform a specific water control task. These control systems provide builders and engineers with simple water control solutions that are easy to install, inspect and maintain.



For illustration only

Typical Application

- On floor, compact pressure zone control system for water cabinets in high-rise buildings
- Technical floor, centralized pressure zones control system
- Critical water supply systems that can be incorporated into multi-branch duty cycled controlled systems for uninterrupted water supply
- Supply line pressure modulation protects buildings from fluctuating or excessive city line pressure



700 Series

Pressure Control


Model WW-72S-B2H-BP

Features and Benefits

- Compact structure offers small footprint for vertical or horizontal installation in tight confined spaces such as water cabinets and technical floors
- Integral factory assembled unit offers easy and simple installation reducing assembly errors and logistics difficulties
- Factory calibrated and adjustable on site, saving time and reducing engineering, operating and inspection workloads
- Two stage redundancy – safe and continuous water supply
- Excellent quality construction materials ensure reliable, resilient and long lasting operation
- Durable, sophisticated and lightweight design ensure minimal cavitation damage and noise even under difficult and highly intensive operation conditions
- Hydrodynamic body and high performance actuator provide an unobstructed flow path with minimal pressure loss and outstanding modulation capability under conditions of high differential-pressure operation
- Near maintenance-free straightforward balanced design including an actuator that can be easily disassembled from the valve body as a separate integral unit for minimal downtime.
- Accurate and reliable pressure reducing control loop ensures long lasting quick response and consecutive modulation
- Linear adjustment pilot allows easy set up and calibration

Technical Data

Table		Kv	A, B (mm)	C (mm)	L (mm)	H (mm)	W (mm)	Weight (kg)	
DN	inch							Flanged	Grooved
40	1½"	42	350	180	205	239	155	9.1	n/a
50	2"	50	350	180	210	244	165	10.6	6
65	2½"	55	350	180	222	257	178	13	8
80	3"	116	370	230	250	305	200	22	10
100	4"	200	395	275	320	366	223	37	16
150	6"	460	430	385	410	492	320	75	52
200	8"	815	475	460	599	584	390	125	95



End Connections:

Flanged: ISO PN16, PN25 (ANSI Class 150, 300)

Threaded: ISO-7-Rp or NPT

Others: Available on request

Pressure Rating: 16, 25 bar (230, 362 psi)

Valve Pattern: Y & Angle

Working Temperature: Water up to 80°C (180°F)

Main Construction Materials:

Body, Cover and Actuator: Ductile Iron

Internals: Stainless Steel, Bronze & Coated Steel

Brass control components / accessories

Copper & Brass tubing & fittings

Optional: Stainless Steel 316

Elastomers: NBR Nylon fabric-reinforced

Coating / colour: Electrostatic Polyester Powder Blue

Optional: Epoxy Fusion-Bonded Blue

How to Order

Please specify the requested valve in the following sequence:

Size	Model	Category	End Connections
1½"	72S-B2H	BP	Flanged ISO-16 16
2"			ISO-25 25
2½"			ABNT16 B6
3"			ABNT25 B2
4"			ANSI150 A5
6"			ANSI300 A3
8"			JIS-16 J6
			Threaded BSP BP
			NPT NP
			Grooved ANSI C606 V1

For other optional materials consult BERMAD



Trädgårdsteknik AB
Helsingborgsvägen 578
262 96 ÄNGELHOLM
Telefon: 0431-222 90
Telefax: 0431-222 70
info@tradgardsteknik.se
www.tradgardsteknik.se
